

## **10,000 PSI HYDRAULIC HOSE**

### **T1040**

### **For Hydraulic Tool and Jack Line Applications**


*4 to 1 Safety Factor*

#### **Thermoplastic Hose Specifications:**

<b>PART #</b>	<b>T1040-04</b>	<b>T1040-04NC</b>	<b>T1040-06</b>
Inside Diameter	.250"	.250"	.375"
Outside Diameter	.540"	.570"	.740"
Minimum Bend Radius	1.5"	1.5"	3.75"
Dynamic Working Pressure	10,000 psi	10,000 psi	10,000 psi
Minimum Burst Pressure	40,000 psi	40,000 psi	40,000 psi
Weight Per Foot	.15	.11	.24
Operating Temperature	-40 to 212 F	-40 to 212 F	-40 to 212 F
Max Temp. Water Based Fluid	158 F	158 F	158 F
Tube	Polyester Elastomer	Polyester Elastomer	Polyester Elastomer
Reinforcement	Wire/Aramid Fiber	Aramid Fiber	Wire/Aramid Fiber
Cover	Polyurethane	Polyurethane	Polyurethane
Fittings	NPT/British/ Metric	NPT/British/ Metric	NPT/British/ Metric

## **10,000 PSI HYDRAULIC HOSE** **H-Jack**

**For Hydraulic Tool and Jack Line Applications**



### **Rubber Hose Specifications:**

<b>PART #</b>	<b>HJack-04</b>	<b>HJack-06</b>
Inside Diameter	.250"	.375"
Outside Diameter	.583"	.740"
Minimum Bend Radius	4.0"	5.0"
Dynamic Working Pressure	10,000 psi	10,000 psi
Minimum Burst Pressure	20,000 psi	20,000 psi
Operating Temperature	-40 to 122 F	-40 to 122 F
Tube	Synthetic Oil Resistant Rubber	Synthetic Oil Resistant Rubber
Reinforcement	2 High Tensile Steel Wire Braids	2 High Tensile Steel Wire Braids
Cover	Synthetic Rubber	Synthetic Rubber
Fittings	1/4" or 3/8" Male NPT	3/8" Male NPT